



Main

| | |
|-----------------------------|-------------------------------|
| Range name | Sedna |
| Function | Single socket-outlet with lid |
| Delivery form | Without frame |
| Outlet poles configuration | 2P + E with shutters |
| Outlet standard description | Pin earth |
| Rated current | 16 A - 250 V AC |
| Cover plate color | White |
| Kind of terminals | Lift terminals |

Complementary

| | |
|---------------------------|---|
| Installation | Flush |
| Power range | 3680 W |
| Terminal capacity | 2 x 2.5 mm ² |
| Wire structure | Flexible Rigid |
| Wire stripping length | 12 mm |
| Material of visible parts | ASA + PC |
| Surface finish | Glossy |
| Fixing mode | Screws Claws, span of claws working range : 54...71 mm |
| Height | 71 mm |
| Width | 71 mm |
| Depth | 50.5 mm |
| Depth of visual part | 20.5 mm |
| Product weight | 0.09772 kg |

Environment

| | |
|-------------------------|-------------|
| Standards | IEC 60884-1 |
| Product certifications | B |
| IP degree of protection | IP44 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 1126 - Schneider Electric declaration of conformity |
| Product end of life instructions | Need no specific recycling operations |